

# SHARKSKIN™

## The Ultimate Roof Underlayment *Ultra*

### SHARKSKIN ULTRA 10 SQ. ROLL

#### Instructions and Information

SHARKSKIN ULTRA™

**Use:** Under tile, metal, slate and asphalt shingle roof systems.

**Roll size:** 48" x 250' approx. Roll weight: 45 lbs. approx.

**Coverage:** approx. 960 sq. ft. per roll or less depending upon overlap and roof design.



**Installation:** SHARKSKIN ULTRA™ roofing underlayment should be installed above ventilated attic spaces in most cases, as it is considered a vapor barrier, check with local building codes. The deck surface must be dry and free of dust, dirt, loose nails, debris and other protrusions. Damaged sheathing must be replaced. SHARKSKIN ULTRA™ is laid horizontally parallel to the eave with the printed side up, and minimum 2-inch (4-inch is recommended) horizontal laps and a minimum 6-inch vertical laps. Use straight blade utility knife or scissors to cut. Overlaps run with the flow of water in a shingling manner. SHARKSKIN ULTRA™ is attached to the roof deck with corrosion-resistant 3/8" roofing nails, or No. 12 gage corrosion-resistant steel or stainless steel shank having 1-inch diameter corrosion resistant metal round cap, tin tag, or plastic round top caps or plastic caps fastened with corrosion resistant staples. The underlayment shall be fastened as necessary to hold in place and to allow for safe walk ability for the installer.

**BE CAREFUL TO OBSERVE SAFE ROOFING CODES & PRACTICES (OSHA). USE CAUTION WHEN WALKING OR STANDING ON SHARKSKIN ULTRA™. COEFFICIENT OF FRICTION MAY CHANGE WITH WET, DUSTY OR ICY CONDITIONS. FAILURE TO USE PROPER SAFETY GEAR AND FOOTWEAR CAN RESULT IN SERIOUS INJURY.**



Florida Building Code  
(FBC) #FL8097

U.S. Patent #6,308,482

**Kirsch Building Products LLC**  
1464 Madera Road  
Suite 367  
Simi Valley, CA 93065  
[www.sharkskin.us](http://www.sharkskin.us)



ESR-1708  
ICC-ES AC188  
ICC-ES AC48  
EXCEEDS ASTM D226

